



## TO WHO IT MAY CONCERN

### Knauf Tiles

- Type: Knauf tiles with PVC- GKB 9.5, GKB 12.5, and GKI 12.5.
- Colors: white (1063), beige (17611) and grey (17612).
- Dimension: 60\*60, thickness 9.5, 12.5- PVC thickness 0.35mm-0.45mm.
- Fire Resistance: B1 based on DIN 4102
- Weight: 7kg/m<sup>2</sup> or 9 kg/m<sup>2</sup>, according to thickness.
- Light Reflection: >7 international woolscale
- Chemical Resistance: Against household chemicals
- Resistance to productivity of the production of bacteria: Good
- Cleaning Resistance: Good
- Moisture Resistance: 25kg/m<sup>2</sup>/24hours in the range of humidity from 98%to 0%.
- Sound Absorption: NCR=0.10 aw=0.13
- Usage: for high humidity, for food production and hospitals.

### Knauf Tiles (Hygena)

- Type: Knauf tiles with PVC- BN. Bio-Pruf®
- Colors: white (1063)
- Dimension: 60\*60, thickness,12.5- PVC thickness 0.35mm-0.45mm
- Fire Resistance: B1 based on DIN 4102
- Weight: 9 kg/m<sup>2</sup>
- Light Reflection: >7 international woolscale
- Chemical Resistance: Against household chemicals
- Anti microbes and antibacterial resistance: excellent and the PVC is certified by Bio-Pruf®.
- Cleaning Resistance: Good
- Moisture Resistance: 25kg/m<sup>2</sup>/24hours in the range of humidity from 98%to 0%.
- Sound Absorption: NCR=0.10 aw=0.13
- Usage: for high humidity, for food production and hospitals.

Technical Department



Knauf Ltd., 6A, Street No. 23, Third Floor,  
Beside Maadi Grand Mall, New Maadi, Cairo – Egypt.  
e-mail: info@knauf-eg.com